



...the choice matters

Electro safe MD555
Electrical switchboard matting

www.matsdirect.co.uk

ASTM D178 /ANSI JS.7 Type 2 Class 4

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	40,000v
Surface proof test	30,000v
Working voltage	26,000v



Colour:	Black
Hardness:	60 shore A
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC
Abrasion Resistance:	2000 mm3

Thickness:	12.5
Roll size (10m x 0.91m):	EX STOCK
Weight/ M2 (kgs - appx):	14.5

MD555 Electrical Matting Performance.

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Cleaning and Maintenance Daily:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquires:

Tel: 0161 797 6785
Fax: 0845 370 6786
E-mail: info@matsdirect.co.uk