



Electro safe MD580
Electrical switchboard matting

...the choice matters

www.matsdirect.co.uk

VDEO 303 Certification

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test 50,000v
Working voltage 1,000v



Colour:	Grey
Hardness:	65 shore A
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC
Abrasion Resistance:	180 mm3

Thickness:	4.0mm
Weight/M2 (Kg- Approx):	4.2 Kg
Roll size (10m x 1m):	EX STOCK
Roll size (10m x 1.2m):	EX STOCK

MD580 Electrical Matting Performance.

Fully branded on reverse
Extremely safe from electrical shock and hard wearing
Positive safe grip from the flutes

Cleaning and Maintenance Daily:

Matting may be washed with soap or a mild non-bleaching detergent.
After washing, the matting should be rinsed thoroughly with water.
Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk