



Electro safe MD574
Electrical switchboard matting

...the choice matters

www.matsdirect.co.uk

Tested & Stamped to European IEC 61111 Class 4 specification

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

| | |
|--------------------|---------|
| Dielectric test | 50,000v |
| Surface proof test | 40,000v |
| Working voltage | 36,000v |



| | |
|---------------------------|-------------|
| Colour: | Grey |
| Hardness: | 65 shore A |
| Tensile: | 6.0 Mp |
| Temperature Range: | -20/+70DegC |

| | |
|--------------------------------|----------|
| Thickness:mm | 4.5 |
| Weight/M2 (Kg- Approx): | 6.1 |
| Roll size (10m x 1.3m): | TO ORDER |

MD574 Electrical Matting Performance.

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Cleaning and Maintenance:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk