



Electro safe MD552  
Electrical switchboard matting

...the choice matters

www.matsdirect.co.uk

**ASTM D178 /ANSI JS.7 Type 2 Class 1**

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	20,000v
Surface proof test	10,000v
Working voltage	7,500v



<b>Colour:</b>	Black
<b>Hardness:</b>	60 shore A
<b>Tensile:</b>	5.0 Mp
<b>Elongation</b>	250%
<b>Temperature Range:</b>	-20/+70DegC
<b>Abrasion Resistance:</b>	180 mm3

<b>Thickness:</b>	4.5mm
<b>Roll size (10m x .91m):</b>	EX STOCK
<b>Roll size (10mx 1.2m):</b>	EX STOCK
<b>Weight/ M2 (kgs - appx):</b>	5.5
<b>Roll size (22.86mx 1.2m):</b>	Available
<b>Roll size (22.86mx .91.m):</b>	Available

**MD552 Electrical Matting Performance.**

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

**Cleaning and Maintenance :**

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

**MatsDirect UK Ltd**  
Unit 2 Bolholt Industrial Park  
Walshaw Road  
Bury, Lancashire  
BL8 1PL UK

**For all enquiries:**

**Tel:** 0044 (0)161-797-6785  
**Fax:** 0044 (0)161-797-6349  
**E-mail:** sales@matsdirect.co.uk