

A new approach to entranceway protection
Satra Tested TM144 for slip resistance.
Diamond entrance door matting modules are a triumph in computer generated, state of the art design and flexibility. Interchangeable modules to maximize wear and easily replaceable at minimal cost thus extending the life cycle of the system. Ensuring the removal of moisture and grit through its unique interactive cleaning action, incorporating over 256 flexible Rubber diamond and 12 carpet pads in every square metre, creating Active Pile Technology APT® with the Nylon carpet fibres.

Manufactured to ISO9002 and conforming to current BS8300 DDA regulations.

Diamond entrance matting is ideal for non-conforming door entrances where traffic does not always flow in a straight line.

Due to its unique design where ever the traffic flows be it left, right or at any angles to the doorway entrance they will always achieve 100% contact with the fibres of the mat making Diamond entrance matting the only true multi-directional Matwell entrance floor mat system.



Colour:	Charcoal, Blue, Green, Red.	Thickness:mm	18, 12
Temperature Range:	-20/+70 DegC	Weight/M2 (Kg- Approx):	11, 7.5
		Module size (100 x 0.5):cm	EX STOCK

MD3000 Diamond Multi-Directional Entrance Matting Performance.

Outstanding soil retention and moisture dispersion properties.

Hard working entrance matting system with over 256 diamonds & 3500 round studs per M2.

Cleaning and Maintenance Daily:

Vacuum clean. An upright unit with a powered cylindrical brush is ideal.