



Electro safe MD557
Electrical switchboard matting

...the choice matters

www.matsdirect.co.uk

ASTM D178 /ANSI JS.7 Type 2

Class 5.1.2.1/ 5.1.2.2/ 5.1.2.3

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	20,000v
Surface proof test	10,000v
Working voltage	7,500v



Colour:	Black
Hardness:	60 shore A
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC
Abrasion Resistance:	200 mm3

Thickness:	4.5mm
Roll size (10m x .91m):	EX STOCK
Thickness:	6.5mm
Roll size (10m x .91m):	EX STOCK
Thickness:	10mm
Roll size (10m x .91m):	EX STOCK

MD557 Electrical Matting Performance.

- Class 5.1.2.1. Ozone resistant
- Class 5.1.2.2. Flame resistant
- Class 5.1.2.3. Oil resistant
- Fully branded on reverse.
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Cleaning and Maintenance:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk