

Thruguard MD7800

Heavy Duty Open Grid Matting

TYPICAL Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT
300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Reference:	Thruguard EMD7800 Aluminium Heavy Duty Open Grid Matting
Height:	12mm/18mm/23mm
Infill Colours available:	To be specified.
Installation:	Recessed in matwell.

DETAILED Specification

Reference:	Thruguard EMD7800 Aluminium Heavy Duty Open Grid Entrance Matting
Conformity:	Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA regulations.
Grid construction:	Aluminium - 80% recycled content in open construction format.
Infil:	To be specified
Total height:	12mm/18mm/23mm
Product Weight (per m2):	14kg/16kg/18kg
Module Size:	Thruguard panels are manufactured specifically to customer requirements. Individual panel widths up to 2200mm left to right as required.
Infil colour options:	To be specified.
UV Resistance:	Yes
Installation:	Recessed in matwell.

Description

Thruguard is a primary matting system for specification in high traffic commercial applications such as retail stores, airports, shopping centres, schools and hospitals where the removal of foot-borne and wheeled-in soilage at entranceways is essential. **Thruguard** will withstand heavy and wheeled traffic use.

The matting can be supplied in single width panels of up to 3500mm for a seamless appearance and can be shaped to the most demanding design requirement.

Entrance MatsDirect Limited
Unit 2, Bolholt Industrial Park
Walshaw Road
Bury
Lancashire BL8 1PL

For all enquiries:

Tel: +44 (0) 161 765 3510
Fax: +44 (0) 161 797 6349
Email: sales@entrancematsdirect.co.uk
Web: www.entrancematsdirect.co.uk