



...the choice matters

Electrosafe 551

Rubber switchboard safety matting

www.matsdirect.co.uk

Fully tested general-purpose safety matting.

Stamped on the reverse every 100cm.

High quality Rubber electrical switch-board matting.

Ideal for use on all 3 phase supply equipment.

Tested to 11,000v.
Working volt test 450v



Colour:	Black
Hardness:	60 shoreA
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC

Thickness:	6.0mm
Roll size (10m x 1m):	EX-STOCK
Roll size (10mx 1.2m):	EX-STOCK
Weight/ M2 (kgs-appx):	6.8

Electrosafe 551 Electrical Matting

Performance. Fully branded on reverse
Protection from electrical shock
Hard wearing
Positive safe grip from the flutes

Cleaning and Maintenance Daily:

Matting may be washed with soap or a mild non-bleaching detergent. After washing the matting should be rinsed thoroughly with water.
Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk