



...the choice matters

Electrosafe 580 VDEO303
Rubber Switchboard Matting

www.matsdirect.co.uk

VDEO 303 Certification

An extremely ultra high specification quality natural Rubber compound. Switchboard safety matting for the prevention of shocks whilst working on live switchboards.

Capable of withstanding the following:

Dielectric test 50,000v
Working voltage 1,000v



Colour:	Grey
Hardness:	65 shore A
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC
Abrasion Resistance:	180 mm3

Thickness:	4.0mm
Weight/M2 (Kg- Approx):	4.2 Kg
Roll size (10m x 1m):	EX STOCK
Roll size (10m x 1.2m):	EX STOCK

MD580 Electrical Matting Performance.

Fully branded on reverse
Extremely safe from electrical shock and hard wearing
Positive safe grip from the fine flutes

Cleaning and Maintenance Daily:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk