



...the choice matters

MD215 Anti-Static

Interlocking Tile

www.matsdirect.co.uk

Manufactured from a high quality soft feel PVC. The ESD floor tiles are moulded using compounds that ensures compliancy with IEC 61340-5-1 for the life of the product, when installed using a suitable earthing (grounding) system.

This product is designed to be used in the electronics industry however it may be used in any industry that requires a floor to ground personnel or equipment.



ESD Floor Tiles

Colours: Grey base/Yellow warning tile

Thickness:mm 7
Weight/Tile (Kg- Approx): 2.2
Tile size (500mm x 500mm): EX STOCK

MD215 ESD Anti-static Interlocking Tile Performance.

- Lightweight.
- Robust precision 'T' connection cut.
- Durable and resilient.
- Multi-directional anti-slip properties.

Colour Fastness

To sunlight, general cleaning and remedial treatment.

Cleaning and Maintenance Daily:

Vacuum clean. Damp mop and rotary scrubber dryer using a ph neutral cleaning solution.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk