

Electrical Rubber matting fully tested in Accordance with BS921/1976

British Standard and stamped on the reverse every 100cm.

A high quality Electrical Rubber safety matting made to exacting standards and fully certified and

Tested to: 15,000v.
Working volt test: 650v.

Also available made specially to order to meet the following specifications:-

BS476: Part 7 1997 class 1 Flame resistance.
BS6853:1999 Annex B.2 Class 1a Smoke Toxicity.
BS6853:1999 Annex D.8.6 Class 1a Smoke Density.

Colour: Black
Hardness: 60 shore
Tensile: 5.0 Mp
Elongation 250%
Temperature Range: -20/+70 DegC
Abrasion Resistance: 180 mm³

Thickness: 9.5mm
Roll size (10m x 0.91cm): EX STOCK
Roll size (10m x 1m): EX STOCK
Roll size (10mx 1.2m): EX STOCK
Weight/ M2 (kgs - appx): 12



MD550 Electrical Matting Performance.

Fully branded on reverse
Extremely safe from electrical shock and hard wearing
Positive safe grip from the flutes

Colour Fastness

To sunlight, general cleaning and remedial treatment

Cleaning and Maintenance Daily:

Vacuum clean. An upright unit with a powered cylindrical brush is ideal.