



...the choice matters

Electrosafe MD552
Earthing Floor matting

www.matsdirect.co.uk

ASTM D178 /ANSI JS.7 Type 1 Class 1

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	20,000v
Surface proof test	10,000v
Working voltage	7,500v



Colour:	Black	Thickness:	4.5mm
Hardness:	60 shore A	Roll size (10m x .91m):	EX STOCK
Tensile:	5.0 Mp	Roll size (10mx 1.2m):	EX STOCK
Elongation	250%	Weight/ M2 (kgs - appx):	5.5
Temperature Range:	-20/+70DegC	Roll size (22.86mx 1.2m):	Available to order
Abrasion Resistance:	180 mm3	Roll size (22.86mx .91.m):	Available to order

MD552 Electrosafe Matting Performance.

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Cleaning and Maintenance :

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk