



...the choice matters

Electrosafe MD554
Earthing Floor matting

www.matsdirect.co.uk

ASTM D178 /ANSI JS.7 Type 1 Class 3

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	40,000v
Surface proof test	30,000v
Working voltage	26,000v



Colour:	Black
Hardness:	60 shore A
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC
Abrasion Resistance:	180 mm3

Thickness:	9.5mm
Roll size (10m x .91m):	EX STOCK
Weight/ M2 (kgs - appx):	9.5

MD554 Electrosafe Matting Performance.

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Colour Fastness

To sunlight, general cleaning and remedial treatment

Cleaning and Maintenance Daily:

Vacuum clean. An upright unit with a powered cylindrical brush is ideal.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk