



...the choice matters

Electrosafe MD557  
Earthing Floor matting

www.matsdirect.co.uk

**ASTM D178 /ANSI JS.7 Type 2 Class 2**

An extremely ultra high specification quality Neoprene Rubber compound safety matting product able to withstand the following:

- Dielectric test 20,000v
- Surface proof test 10,000v
- Working voltage 7,500v



**Colour:** Black  
**Hardness:** 60 shore A  
**Tensile:** 5.0 Mp  
**Elongation** 250%  
**Temperature Range:** -20/+70 DegC  
**Abrasion Resistance:** 200 mm3

**Thickness:** 4.5mm  
**Roll size (10m x .91m):** EX STOCK  
**Thickness:** 6.5mm  
**Roll size (10m x .91m):** EX STOCK  
**Thickness:** 10mm  
**Roll size (10m x .91m):** EX STOCK

**MD557 Electrosafe Matting Performance.**

- Class 5.1.2.1. Ozone resistant**
- Class 5.1.2.2. Flame resistant**
- Class 5.1.2.3. Oil resistant**

Fully branded on reverse.

Extremely safe from electrical shock and hard wearing Positive safe grip from the flutes

**Cleaning and Maintenance:**

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water.

Matting should be air dried, but not such that the matting temperature exceeds 65°C.

**MatsDirect UK Ltd**  
 Unit 2 Bolholt Industrial Park  
 Walshaw Road  
 Bury, Lancashire  
 BL8 1PL UK

**For all enquiries:**

**Tel:** 0044 (0)161-797-6785  
**Fax:** 0044 (0)161-797-6349  
**E-mail:** sales@matsdirect.co.uk