

Rubber Modular Entrance Matting

TYPICAL Specification

**N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT
300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS**

Manufacturer: Matsdirect UK Limited, Unit 2 Bolholt Industrial Park, Walshaw Road, Bury, Lancashire BL8 1PL
Tel: 0161 797 6785 Fax: 0161 797 6349
Email: sales@matsdirect.co.uk
Website: www.matsdirect.co.uk

Reference: MD1000 Matrix Modular Entrance Matting
Height (select as required): 18mm/12mm
Installation: Recessed in matwell or surface-laid with ramping frame.

DETAILED Specification

Reference: MD1000 Matrix Modular Entrance Matting
Conformity: Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA requirements regulations. **Module construction:** SBR rubber moulded
Total height (select as required): 18mm/12mm
Weight: 13kg/9kg
Module Size: 100cm left to right x 50cm front to back
Slip Resistance: Tested to SATRA TM144
Classification: Tested to BS EN 1307
Fire rating: Hot Metal Nut BS4790 (Low Radius)
Installation: Recessed in matwell or surface-laid with ramping frame.

Description

Matrix is a primary matting system for specification in commercial applications where the removal of footborne and wheeled-in soilage at entranceways is essential.

The matting modules are supplied as solid moulded units measuring 100cm left to right x 50cm front to back and 18mm or 12mm thick. They may be surface laid or recess fitted as required. The subfloor should be good and flat so as to provide a safe walking surface when the modules are in place.

Matrix entrance matting has been specially developed to be used in matwells that are covered, inside or mostly protected from the weather. Each square metre has over 5,000 round studs and 22 high absorbency carpet strips to give an excellent cleaning and drying surface along with a safe grip feeling when traversed.