

Aluminium Grid Panel Entrance Matting TYPICAL Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer:	Matsdirect UK Limited, Unit 2 Bolholt Industrial Park, Walshaw Road, Bury, Lancashire BL8 1PL Tel: 0161 797 6785 Fax: 0161 797 6349 Email: sales@matsdirect.co.uk Website: www.matsdirect.co.uk
Reference:	MD7000 STRATOS Grid Entrance
Matting Height (select as required):	18mm/11mm
Installation:	Recessed in matwell or surface-laid with ramping frame.

DETAILED Specification

Reference:	MD7000 STRATOS Aluminium Grid Entrance Matting
Conformity:	Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA regulations.
Grid construction:	Aluminium - minimum 80% recycled content in closed construction format.
Yarn:	Polypropylene
Total height (select as required):	11mm or 17mm
Module Size:	STRATOS panels are manufactured specifically to customer requirements. Panels widths up to 4000mm left to right as required.
Wiper colour options:	Black, anthracite, grey, blue, green, olive, brown, beige, natural, burgundy, red, tan.
Fire rating:	Hot Metal Nut BS4790: 1987 (1996)
Installation:	Recessed in matwell or surface-laid with ramping frame.

Description

STRATOS is a primary matting system for specification in commercial applications where the removal of footborne and wheeled-in soilage at entranceways is essential in retail stores, airports, shopping centres, schools and hospitals. STRATOS will withstand heavy and wheeled traffic use.

The matting can be supplied in single width panels of up to **4 M** for a seamless appearance and can easily be supplied to the most demanding design requirement.

The modules may be surface laid or recess fitted as required. All contact strips are easily replaceable for refurbishment purposes.

The wiper material is also available in sheet form as a secondary barrier matting system to complement and coordinate with the STRATOS primary matting system.