

## Aluminium Open Grid Entrance Matting TYPICAL Specification

### N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

**Manufacturer:** Matsdirect UK Limited, Unit 2 Bolholt Industrial Park, Walshaw Road, Bury, Lancashire BL8 1PL  
Tel: 0161 797 6785 Fax: 0161 797 6349  
Email: [sales@matsdirect.co.uk](mailto:sales@matsdirect.co.uk)  
Website: [www.matsdirect.co.uk](http://www.matsdirect.co.uk)

**Reference:** MD7800 THRUGUARD Open Grid Entrance  
**Matting Height (select as required):** 12mm, 18mm, 23mm  
**Installation:** Recessed in matwell .

### DETAILED Specification

**Reference:** MD7800 THRUGUARD Open Grid Entrance Matting

**Conformity:** Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA regulations.

**Grid construction:** Aluminium - 80% recycled content in open construction format.

**Infil:** To be specified

**Total height:** 12mm/18mm/23mm

**Product Weight (per m2):** 14kg/16kg/18kg

**Module Size:** Thruguard panels are manufactured specifically to customer requirements. Individual panel widths up to 2200mm left to right as required.

**Infil colour options:** To be specified.

**UV Resistance:** Yes

**Installation:** Recessed in matwell.

### Description

**Thruguard** is a primary matting system for specification in high traffic commercial applications such as retail stores, airports, shopping centres, schools and hospitals where the removal of foot-borne and wheeled-in soilage at entranceways is essential. Thruguard will withstand heavy and wheeled traffic use.

The matting can be supplied in single width panels of up to 3500mm for a seamless appearance and can be shaped to the most demanding design requirement.