



...the choice matters

Electro safe MD551
Electrical switchboard matting

www.matsdirect.co.uk

Fully tested general-purpose safety matting and stamped on the reverse every 100cm.

High quality Rubber electrical safety matting made to exacting standards and fully certified and tested to 11,000v. Working volt test 450v



Colour:	Black
Hardness:	60
	shoreA
Tensile:	5.0 Mp
Elongation	250%
Temperature Range:	-20/+70 DegC

Thickness:	6.0mm
Roll size (10m x 1m):	EX-STOCK
Roll size (10mx 1.2m):	EX-STOCK
Weight/ M2 (kgs-appx):	6.8

MD551 Electrical Matting Performance.

- Fully branded on reverse
- Protection from electrical shock
- Hard wearing
- Positive safe grip from the flutes

Cleaning and Maintenance Daily:

Matting may be washed with soap or a mild non-bleaching detergent. After washing the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk