



Electro safe MD574  
Electrical switchboard matting

...the choice matters

www.matsdirect.co.uk

**Tested & Stamped to European IEC 61111 Class 4 specification**

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	50,000v
Surface proof test	40,000v
Working voltage	36,000v



<b>Colour:</b>	Grey
<b>Hardness:</b>	65 shore A
<b>Tensile:</b>	6.0 Mp
<b>Temperature Range:</b>	-20/+70DegC

<b>Thickness:mm</b>	4.5
<b>Weight/M2 (Kg- Approx):</b>	6.1
<b>Roll size (10m x 1.3m):</b>	TO ORDER

**MD574 Electrical Matting Performance.**

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

**Cleaning and Maintenance:**

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

**MatsDirect UK Ltd**  
Unit 2 Bolholt Industrial Park  
Walshaw Road  
Bury, Lancashire  
BL8 1PL UK

**For all enquiries:**

**Tel:** 0044 (0)161-797-6785  
**Fax:** 0044 (0)161-797-6349  
**E-mail:** sales@matsdirect.co.uk