



...the choice matters

Surestat

MD211

Anti-Static Bench Rubber Matting

www.matsdirect.co.uk

To prevent minor shocks whilst working with electronic components and materials that create static build up, supplied with or without studs.

ESD rubber matting most suitable for bench coverings. The 2mm thick static dissipative matting has excellent heat / chemical resistance.

The characteristics include - dissipative surface resistivity, static decay rate complying with accepted standards, durable and flexible with excellent lay flat properties.

Surface resistance and resistance to ground:  $5 \times 10^6 - 5 \times 10^8$  Standard IEC 61340- 5-1 Charge decay time: FTM 101C No: 4046 (5000v - 500v) <0.009 sec



<b>Colour:</b>	Grey, Blue, Green.	<b>Thickness:mm</b>	2
<b>Custom Cut Mat Sizes Available.</b>		<b>Weight/M2 (Kg- Approx):</b>	3
<b>Plugs, Cables, Studs, Guns Also Available.</b>		<b>Roll size (10m x 1.22m):</b>	EX STOCK

**MD211 Anti-static Bench Matting Performance.**

Very good slip resistance.  
Extremely safe from static shock and hard wearing  
Excellent lay flat properties.

**CUT TO SIZE & FREE STUD SERVICE AVAILABLE**

**Colour Fastness**

To sunlight, general cleaning and remedial treatment

**Cleaning and Maintenance Daily:**

Vacuum / wipe clean.

**MatsDirect UK Ltd**

Unit 2 Bolholt Industrial Park  
Walshaw Road  
Bury, Lancashire  
BL8 1PL UK

**For all enquiries:**

**Tel:** 0044 (0)161-797-6785  
**Fax:** 0044 (0)161-797-6349  
**E-mail:** sales@matsdirect.co.uk