

High Quality SBR synthetic/natural Rubber matting.  
A heavy duty and robust runner Rubber matting offers exceptional wear characteristics.

Ideal for lift floors, ramps, escalator or bridge aprons and building access door points for heavy wheeled vehicles or trolleys.  
The ribbed profile offers sure footedness and also acts as a scraper to trap water and debris.

Suretred matting can be stuck directly over existing hard flooring in most cases, or installed as a new finish to any doorway apron.

It may be applied indoors or outdoors.  
Available in a stock range of colours and thicknesses for a variety of applications.



**Colours:** Black, Green, Grey, Blue  
Brown @ 5mm Thickness  
**Hardness:** 70 Shore A  
**Tensile:** 3 Mpa  
**Elongation:** 150%  
**Temperature Range:** -20/+70DegC  
**Abrasion Resistance:** 300 mm<sup>3</sup>

**Thickness:mm** 4, 6, 8, 9.5  
**Weight/M2 (Kg- Approx):** 3.75 @ 3mm  
**Roll size (10m x 1m):** EX STOCK  
**Roll size (10m x 1.2m):** EX STOCK

**Custom Cut Mat Service Available**

### MD540 Suretred Broad Rib Matting Performance.

Excellent soil & moisture retention. Positive grip from the ribs.  
Hard wearing Rubber matting.

### Colour Fastness

To sunlight, general cleaning and remedial treatment.

### Cleaning and Maintenance:

Vacuum clean. Warm water mop with a mild detergent.