

Rubber Modular Multi-directional Entrance Matting

TYPICAL Specification

**N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT
300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS**

Manufacturer: Matsdirect UK Limited, Unit 2 Bolholt Industrial Park, Walshaw Road, Bury, Lancashire BL8 1PL
Tel: 0161 797 6785 Fax: 0161 797 6349
Email: sales@matsdirect.co.uk
Website: www.matsdirect.co.uk

Reference: MD3000 Diamond Multi-directional Modular Entrance Matting
Height (select as required): 18mm/12mm
Installation: Recessed in matwell or surface-laid with ramping frame.

DETAILED Specification

Reference: MD3000 Diamond Multi-directional Modular Entrance Matting

Conformity: Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA requirements regulations.

Module construction: SBR rubber moulded

Total height (select as required): 18mm/12mm

Weight: 13kg/9kg

Module Size: 100cm left to right x 50cm front to back

Slip Resistance: Tested to SATRA TM144

Classification: Tested to BS EN 1307

Fire rating: Hot Metal Nut BS4790 (Low Radius)

Installation: Recessed in matwell or surface-laid with ramping frame.

Description

Diamond Multi-directional is a primary matting system for specification in commercial applications where the removal of footborne and wheeled-in soilage at entranceways is essential.

The matting modules are supplied as solid moulded units measuring 100cm left to right x 50cm front to back and 18mm or 12mm thick. They may be surface laid or recess fitted as required. The subfloor should be good and flat so as to provide a safe walking surface when the modules are in place.

Diamond Multi-directional entrance matting has been specially developed to be used in matwells where traffic moves in any direction and that are covered, inside or mostly protected from the weather. Each square metre has over 1,296 round studs, 128 diamond studs and 8 high absorbency carpet pads to give an excellent cleaning and drying surface along with a safe grip feeling when traversed from any direction.