

Aluminium Open Grid Entrance Matting TYPICAL Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Matsdirect UK Limited, Unit 2 Bolholt Industrial Park, Walshaw Road, Bury, Lancashire BL8 1PL
Tel: 0161 797 6785 Fax: 0161 797 6349
Email: sales@matsdirect.co.uk
Website: www.matsdirect.co.uk

Reference: MD7800 THRUGUARD Open Grid Entrance
Matting Height (select as required): 12mm, 18mm, 23mm
Installation: Recessed in matwell .

DETAILED Specification

Reference: MD7800 THRUGUARD Open Grid Entrance Matting

Conformity: Manufactured to ISO9002 Standard. Conforms to current BS8300 DDA regulations.

Grid construction: Aluminium - 80% recycled content in open construction format.

Infil: To be specified

Total height: 12mm/18mm/23mm

Product Weight (per m2): 14kg/16kg/18kg

Module Size: Thruguard panels are manufactured specifically to customer requirements. Individual panel widths up to 2200mm left to right as required.

Infil colour options: To be specified.

UV Resistance: Yes

Installation: Recessed in matwell.

Description

Thruguard is a primary matting system for specification in high traffic commercial applications such as retail stores, airports, shopping centres, schools and hospitals where the removal of foot-borne and wheeled-in soilage at entranceways is essential. Thruguard will withstand heavy and wheeled traffic use.

The matting can be supplied in single width panels of up to 3500mm for a seamless appearance and can be shaped to the most demanding design requirement.